

SECTION: MANUFACTURER:

Strike First Corporation
 777 Tapscott Road
 Scarborough, Ontario
 M1X 1A2
 Phone: 1-416-299-7767

PRODUCT IDENTIFICATION

ABC SUPER 90 DRY CHEMICAL
 Multi-Purpose Dry Chemical
 Fire Extinguisher

EMERGENCY PHONE:
Canutec: 1-613-996-6666

SECTION: HAZARDOUS INGREDIENTS

CHEMICAL	CAS #	%	*ACGIH mg/m3		*OSHA mg/m3			OTHER
			TLV	STEL	PEL	STEL	IDLH	
Mono Amm	7722-76-1	95*						
Mica	12001-26-2	<3	3	NE	3	NE	NE	NE
Attaclay	8031-18-3	<3	NE	NE	NE	NE	NE	NE
Silicone Oil	63148-57-2	<1	NE	NE	NE	NE	NE	NE
Calcium Car	471-34-1	<1	NE	NE	NE	NE	NE	NE
Silica	112926-00-8	<1	2	NE	6	NE	NE	NE
Yellow Pigm	5468-75-7	<1	NE	NE	NE	NE	NE	NE

*ACGIH TLV for particulars, not otherwise classified = 10; OSHA PEL for particulars not otherwise regulated, Total dust =15 Respirable fraction 5.
 NE = Not established

SECTION: PHYSICAL DATA

BOILING POINT	Not applicable
VAPOR PRESSURE	Not applicable
VAPOR DENSITY	Not applicable
SOLUBILITY IN WATER	Not soluble. Water repellent coating.
SPECIFIC GRAVITY	Approximately 0.88
PERCENT VOLATILE BY VOLUME	Not applicable
EVAPORATION RATE	Not applicable
pH: (10% solution)	Approximately 9-10
APPEARANCE & COLOR	This material is a finely divided yellow powder.

SECTION: FIRE AND EXPLOSION DATA

FLASH POINT	Not applicable
FLAMMABLE LIMITS	Lower (LEL) Not applicable Upper (LEL) Not applicable
EXTINGUISHING MEDIA	None This product is a fire extinguishing agent.
SPECIAL FIREFIGHTING PROCEDURES	Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment.

SECTION: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	*ACGIH TLV for particulars, Not otherwise classified = 10
OSHA PEL	For particulars not otherwise regulated; Total Dust =15, Respirable Fraction 5.
EFFECTS OF OVEREXPOSURE	
Acute	This extinguishing material presents only a slight risk of causing acute health effects. If such effects occur, they will be in the form of mild irritation of the skin, nose, or throat and moderate irritation of the eyes. If ingested, this product may cause an upset stomach.
Chronic	This product is not known to cause chronic illnesses or diseases.

EMERGENCY FIRST-AID PROCEDURES

SKIN EXPOSURE	If spilled on skin, immediately begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.
EYE EXPOSURE	If chemical is splashed in eyes, open victim's eyes while under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes.

SECTION: **EMERGENCY FIRST-AID PROCEDURES**

INHALATION	If chemical is inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.
------------	--

SECTION: **REACTIVITY DATA**

STABILITY	Stable
INCOMPATIBILITY	Strong acids. Reacts violently with lithium.
HAZARDOUS DECOMPOSITION PRODUCT	Carbon monoxide and carbon dioxide
HAZARDOUS POLYMERIZATION	Will not occur

SECTION: **SPILL OR LEAK PROCEDURES**

SMALL SPILLS	Sweep up the spilled solid and place all spill residue in a double plastic bag and seal.
LARGE SPILLS	If it is determined that exposure guidelines for nuisance particulates - 10 mg/m ³ (total particulates) or 5 mg/m ³ (respirable particulates) is exceeded use Level C: triple gloves (rubber gloves with nitrile gloves, over latex gloves), chemically resistant suit and boots, hard hat, and air purifying respirator with a HEPA filter. Sweep or vacuum. Dispose of in accordance with Federal, Provincial and local hazardous waste disposal regulations.

SECTION: **SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION	Respiratory protection is not expected to be needed. Maintain airborne contaminant concentrations below guidelines for nuisance particulates: (see Section 5)
VENTILATION	Use with adequate ventilation. Use a mechanical fan or vent area to outside.
PROTECTIVE GLOVES	Wear rubber gloves for routine industrial use.
EYE PROTECTION	Safety glasses.
OTHER PROTECTIVE EQUIPMENT:	Use body protection appropriate for task.

SECTION: **SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

All employees who handle this material should be trained to handle it safely. Avoid breathing dusts generated by this product.
Avoid getting chemicals ON YOU or IN YOU.

OTHER PRECAUTIONS: None

Fire extinguishers are designed and produced for the specific purpose of providing a safe and efficient safety tool to be used only in the fighting of fires. Improper or careless use may cause severe bodily injury and/or property damage.

Contents are under pressure which is necessary to deliver the contained extinguishing agent to the fire source.

- Contents under pressure. Do not puncture, incinerate or discharge into another person's face.
- Do not store at high temperatures above 120 degrees Fahrenheit or 49 degrees Celcius.
- Keep away from children.
- Avoid inhaling the extinguishing agent. Avoid inhaling smoke and fumes - all fires release toxic substances that are hamful. DO NOT remain in a closed area after use: evacuate the area immediately and ventilate thoroughly before re-entering.
- Although extinguishing agents are non toxic when used properly, contact with them may cause irritation to eyes, nose, throat and other allergic symptoms.